
THE NUTTY COMPANY INC
FASTENER SPECIALISTS SINCE 1977


19 Seemans Lane • Milford, CT 06460 USA
203.877.1709 • 1.800.4NUTTY.1 • Fax 203.735.1097
sales@nutty.com • www.nutty.com



PRODUCT DATA SHEET

Steel Ribbed Rivet Nuts – Metric Sizes

1.0 Dimensions & Hole Sizes (millimeters)






- **Large flange, ribbed body**, open end.
- Ribs bite into the hole wall for **higher spin-out (torque-out) resistance** than a smooth rivet nut.
- Large flange spreads the load for better **push-out** strength.
- Adds strong, reusable threads to thin sheet, tube and extrusions.
- Installs from **one side** – no back-side access needed.
- Steel is **stronger than aluminum** for higher-load threads.
- Sets with any manual or pneumatic rivet nut tool.

A body length (±0.38) **B** head diameter (±0.25) **C** head height (±0.08) **D** body diameter, max.

Stock No.	Thread Size	Grip Range Min – Max	A Body Length	B Head Dia.	C Head Height	D Body Dia. Max	Hole Size Min – Max	Drill Size (mm)
SRRNM4S	**M4 x 0.7**	0.5 – 2.0 (.020 – .079")	10.67	9.91	0.76	6.73	6.75 – 6.90	**6.75**
SRRNM4L	**M4 x 0.7**	2.0 – 3.3 (.079 – .130")	11.94	9.91	0.76	6.73	6.75 – 6.90	**6.75**
SRRNM5S	**M5 x 0.8**	0.5 – 3.3 (.020 – .130")	12.07	10.54	0.76	7.52	7.60 – 7.75	**7.6**
SRRNM5L	**M5 x 0.8**	3.3 – 5.7 (.130 – .224")	14.86	10.54	0.76	7.52	7.60 – 7.75	**7.6**
SRRNM6S	**M6 x 1.0**	0.7 – 4.2 (.028 – .165")	14.73	12.70	0.76	9.91	10.00 – 10.15	**10.0**
SRRNM6L	**M6 x 1.0**	4.2 – 6.6 (.165 – .260")	17.27	12.70	0.76	9.91	10.00 – 10.15	**10.0**
SRRNM8S	**M8 x 1.25**	0.7 – 3.8 (.028 – .150")	17.53	17.40	0.89	13.46	13.50 – 13.65	**13.5**
SRRNM8L	**M8 x 1.25**	3.8 – 7.9 (.150 – .311")	20.45	17.40	0.89	13.46	13.50 – 13.65	**13.5**
SRRNM10S	**M10 x 1.5**	0.7 – 3.8 (.028 – .150")	17.53	17.40	0.89	13.46	13.50 – 13.65	**13.5**
SRRNM10L	**M10 x 1.5**	3.8 – 7.9 (.150 – .311")	20.45	17.40	0.89	13.46	13.50 – 13.65	**13.5**

Dimensions in millimeters (inch grip in parentheses). Metric threads are Class 6H. S = short grip, L = long grip. Grip range = total thickness of all material being joined. Contact us for other sizes, U.S. sizes or aluminum rivet nuts.

2.0 Installation



1. **Drill the hole.** Drill the hole to the **drill size** in the table. Deburr, and make sure the panel is flat.
2. **Thread on.** Thread the rivet nut onto the tool mandrel until the flange sits against the nosepiece.
3. **Insert.** Push the rivet nut into the hole until the flange sits flat on the panel. Hold the tool square to the panel.
4. **Set.** Squeeze the tool: the body collapses behind the panel and locks it in place. Then unscrew the mandrel – the rivet nut is now a permanent threaded hole.
5. **Fasten.** Attach your part with a bolt or screw of the same thread. Do not over-tighten.

3.0 Material & Specifications

Property	Specification
Type	Large flange, ribbed body, open end
Material	Steel
Finish	Zinc plated
Thread	ISO metric coarse, Class 6H
Sizes	M4, M5, M6, M8, M10

4.0 Common Uses

- Sheet metal enclosures, panels and cabinets
- Steel tube, frames and brackets
- Truck bodies, trailers and RVs
- Machinery guards, racks and equipment
- Signs, lighting and electrical boxes
- Fiberglass and plastic panels

5.0 Tips for a Good Install

- Pick the grip range that matches the **total thickness** of the material. Short (S) and long (L) lengths cover different grips – check the table.
- Hole size matters: too big and the nut can spin, too small and it will not seat. Use the drill size listed.
- Set the tool stroke so the nut is fully set but the threads are not stretched. Test on scrap first.
- Use the correct mandrel and nosepiece for each thread size. Heavy-duty or pneumatic tools are best for M8 and M10.
- Steel rivet nuts are best in steel and other strong materials. In aluminum or where corrosion is a concern, use aluminum rivet nuts to avoid galvanic corrosion.

Disclaimer: The above is a compilation of data from various industry standards. The Nutty Company, Inc. has made every effort to present the data accurately. However, The Nutty Company, Inc. cannot be held liable for any claim traceable to any errors, typographical or otherwise, contained herein.



Need rivet nut tools or a size you don't see?
Call 203.877.1709 or email sales@nutty.com – shop online at nutty.com