



FLAT HEADS FOR MACHINE SCREWS

Nominal Size	A		H		J		T		M		G	N	Phillips Driver Size	
	Head Diameter		Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess					
									Diameter		Depth	Width		
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min		
0	.119	.099	.035	.026	.023	.016	.015	.010	.069	.056	.043	.014	0	
1	.146	.123	.043	.033	.026	.019	.019	.012	.077	.064	.051	.015	0	
2	.172	.147	.051	.040	.031	.023	.023	.015	.102	.089	.063	.017	1	
4	.225	.195	.067	.055	.039	.031	.030	.020	.128	.115	.089	.018	1	
5	.252	.220	.075	.062	.043	.035	.034	.022	.154	.141	.086	.027	2	
6	.279	.244	.083	.069	.048	.039	.038	.024	.174	.161	.106	.029	2	
8	.332	.292	.100	.084	.054	.045	.045	.029	.189	.176	.121	.030	2	
10	.385	.340	.116	.098	.060	.050	.053	.034	.204	.191	.136	.032	2	
12	.438	.389	.132	.112	.067	.056	.060	.039	.268	.255	.156	.035	3	
1/4	.507	.452	.153	.131	.075	.064	.070	.046	.283	.270	.171	.036	3	
5/16	.635	.568	.191	.165	.084	.072	.088	.058	.365	.352	.216	.061	4	
3/8	.762	.685	.230	.200	.094	.081	.106	.070	.393	.380	.245	.065	4	
1/2	.875	.775	.223	.186	.106	.091	.103	.065	.424	.411	.276	.069	4	