








ACORN NUT 							
Catalog Number	Anchor Size Hole Dia.	Bolt Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
2505	1/4"	3/16"	5/8"	1/2"	1/8"	500	952
2513	1/4"	3/16"	1-3/8"	1"	3/8"	1364	952
2522	1/4"	3/16"	2-1/4"	1"	1-1/4"	1364	952
2530	1/4"	3/16"	3"	1"	1-3/4"	1364	952
2546	1/4"	3/16"	4-3/4"	1"	3-3/4"	1364	952


TIE WIRE 							
Catalog Number	Anchor Size Hole Dia.	Bolt Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
3114TW	5/16"	1-1/2"	1-1/2"	1/4" Hole		2522	1675

HEX NUT 							
Catalog Number	Anchor Size Hole Dia.	Bolt Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
3111	5/16"	1/4"	1-1/8"	1"	1/8"	2522	1675
3114	5/16"	1/4"	1-1/2"	1"	1/2"	2522	1675
3124	5/16"	1/4"	2-1/2"	1"	1-1/2"	2522	1675
3717	3/8"	5/16"	1-7/8"	1-1/4"	5/8"	2314	3793
3730	3/8"	5/16"	3"	1-1/4"	1 3/4"	2314	3793
3740	3/8"	5/16"	4"	1-1/4"	2-3/4"	2314	3793
5022	1/2"	3/8"	2-1/4"	1-1/2"	3/4"	3008	5344
5026	1/2"	3/8"	2-3/4"	1-1/2"	1-1/4"	3008	5344
5040	1/2"	3/8"	4"	1-1/2"	2-1/2"	5625	7092
5060	1/2"	3/8"	6"	1-1/2"	4-1/2"	5625	7092
6222	5/8"	1/2"	2-1/4"	2"	1/4"	3404	5625
6230	5/8"	1/2"	3"	2"	1"	3404	5625
6242	5/8"	1/2"	4-1/4"	3-1/2"	3/4"	8392	10955

FLAT HEAD-SLOTTED 						
Catalog Number	Anchor Size Hole Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
2513F	1/4"	1-3/8"	1"	3/8"	1364	952
2520F	1/4"	2"	1"	1"	1364	952
2520FT	1/4"	2"	1"	1"	1364	952
2530F	1/4"	3"	1"	2"	1364	952
2540F	1/4"	4"	1"	3"	1364	952
2552F	1/4"	5-1/4"	1"	4-1/4"	1364	952
3124F	5/16"	2-1/2"	1"	1-1/2"	2522	1675
3134F	5/16"	3-1/2"	1"	2-1/2"	2522	1675
3150F	5/16"	5"	1"	4"	2522	1675
3726F	3/8"	3"	1-1/4"	1-1/2"	2314	3793
3740F	3/8"	4"	1-1/4"	2-3/4"	2314	3793
3750F	3/8"	5"	1-1/4"	3-3/4"	2314	3793
3750FT*	3/8"	5"	1-1/4"	3-3/4"	2314	3793
3760F	3/8"	6"	1-1/4"	4-3/4"	2314	3793
3770	3/8"	7"	1-1/4"	5-3/4"	2314	3793

6256	5/8"	1/2"	5-3/4"	3-1/2"	2-1/4"	8392	10955
7524	3/4"	5/8"	2-1/2"	2"	1/2"	5062	10955
7542	3/4"	5/8"	4-1/4"	3-1/2"	3/4"	8433	9413
7554	3/4"	5/8"	5-1/2"	3-1/2"	2"	8433	10452
7562	3/4"	5/8"	6-1/4"	3-1/2"	2-3/4"	8433	10452
7580	3/4"	5/8"	8"	3-1/2"	4-1/2"	8433	10452

ROUND HEAD - SLOTTED 						
Catalog Number	Anchor Size Hole Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
2512R	1/4"	1-1/4"	1"	1/4"	1364	952
2520R	1/4"	2"	1"	1"	1364	952
2526R	1/4"	2-3/4"	1"	1-3/4"	1364	952
2536R	1/4"	3-3/4"	1"	2-3/4"	1364	952
2550R	1/4"	5"	1"	4"	1364	952
3123R	5/16"	2-3/8"	1"	1-3/8"	2522	1675
3133R	5/16"	3-3/8"	1"	2-3/8"	2522	1675
3724R	3/8"	2-1/2"	1-1/4"	1-1/4"	2314	3793
3736R	3/8"	3-3/4"	1-1/4"	2-1/2"	2314	3793

STUD BOLT+ 							
Catalog Number	Anchor Size Hole Dia.	Bolt Dia.	Effective Anchor Length	Minimum Depth In Hole	Fastens Material Up To	Pull Out++	Shear++
2513-1	1/4"	3/16"	1-3/8"	1-3/8"	1"	1364	952
3114-1	5/16"	1/4"	1-1/2"	1-1/2"	1"	2522	1675
3717-1	3/8"	5/16"	1-7/8"	1-7/8"	1"	2314	3793
5022-1	1/2"	3/8"	2-1/4"	2-1/4"	1"	3008	4058
5022-2	1/2"	3/8"	2-1/4"	2-1/4"	2"	3008	4058
6222-2	5/8"	1/2"	2-1/4"	2-1/4"	2"	3404	7092
7524-2	3/4"	5/8"	2-1/2"	2-1/2"	2"	5062	10955

*-Smaller Diameter Head for Threshold and Window Applications **TW**- Tie Wire **F**- Flat Head Slotted **FT**- Flat Head Threshold **FP**- Flat Head Phillips

R- Round Head Slotted **RP**- Round Head Phillips **FS**- Flat Head Stainless **RS**- Round Head Stainless **C**- Coupling Nut **SS**- Stainless Steel

The Nutty Company, Inc.